

3000W High Power Diode Laser

BDL-CW3000



FEATURES:

- ◆ Good power stability
- ◆ Good system reliability
- ◆ Easy-to-use control
- ◆ Cost effective and maintenance free


APPLICATION:

- ◆ Laser welding
- ◆ Laser cladding
- ◆ Surface treatment
- ◆ Laser edge banding

BWT high power diode lasers have high electro-optical efficiency and lower power consumption compared to traditional lasers. Due to the flexible fiber output, BWT high power diode lasers can easily integrated to the equipment. The two operation modes, CW and modulation, minimize heat-affected zone. Reliable performance, modular and all-fiber design, and robust case enclosing all optical and electronic components ensure that they can be used under strict industrial conditions.

BTW high power diode lasers can be used in wide application like laser welding, laser cladding, surface treatment, laser edge banding, etc. The lasers can process various types of metal.


BTW professional laser application team, with good knowledge and experience, provides the best laser system solution for our customers all around the world.



3000W High Power Diode Laser

BDL-CW3000



Optical Character	
Power	3000 W
Wavelength	950±50 nm
Output Fiber Core Diameter	600 μm
Output Cable Length	10m or customized
Output Cable Connector	QBH
Aiming Beam	Red
Operation Mode	CW or modulation
Polarization	Random
Power Stability (25°C)	< ±1.5% (2h)
Power Adjustment Scope	10%-100%
Max Modulation Frequency	5kHz
Size and Weight	
Physical Size (H×W×D)	80mm*402mm*466mm
Weight	25 kg
Electronic Character	
Power Supply	380±20 V, AC, PE, 50/60 Hz
Power Consumption	10.0 kW
Control Interface	RS232/AD
Water Cooling Parameters	
Minimum Water Cooling Capacity	7.0 kW
Temperature Settings	25°C (Laser Module), 30°C (QBH)
Cooling Tubes Size	I.D. Φ19 mm
Cooling Water Flow Rate (Laser)	>25 L/min
Cooling Water Flow Rate (QBH)	1.5~2.0 L/min



3000W High Power Diode Laser

BDL-CW3000

DEMINSIONS (mm)



Declaration: information and specifications contained herein are deemed to be reliable and accurate. BWT Tianjin Ltd. reserves the right to change, alter or modify the design and specifications of these products at any time without notice.