





Diode Laser System

DS3-41624-LD



Features:


- ♦ 976nm wavelength
- ♦ 300W output power
- ♦ 200μm fiber core diameter
- ♦ 0.22 NA

Applications:

- ♦ Plastic Welding
- ♦ 3D Printing
- ♦ Soldering

BWT, founded in 2003, is committed to the mission of "let the dream drive the light", the vision of becoming the "Global leader in laser solutions", and the value of "Outstanding innovation", providing diode laser, fiber laser, ultra-fast laser products and solutions to global customers.

The company pursues continuous innovation and insists on autonomous and controllable advanced process and technology. With Beijing headquarters as the core, BWT has successively established production and R&D centers in Jiangsu, and Shenzhen, and Invested in the construction of an automated and intelligent production base in Tianjin. To build a high level of technical strength and product quality, BWT set up a German subsidiary in 2020, and taking a solid step for the internationalization of R&D, production and technological innovation.



Diode Laser System


DS3-41624-LD

Specifications (25°C)		Unit	DS3-41624-LD
Optical Data ⁽¹⁾	CW Output Power	W	300
	Center Wavelength	nm	976±10
	Output Power Instability	%	±3 (5 hours)
	Power Range	%	10-100
Fiber Data	Core Diameter	μm	200
	Numeric Aperture	-	0.22
	Fiber Length	m	2 or Customized
	Fiber Termination	-	HP-SMA905 or Customized
Electrical Data	Power Supply	V	100~240 (50-60Hz)
	Power Consumption	W	<800
	Drive Mode	-	Constant current
	Emission Mode	-	CW or Modulated
	Control Mode	-	RS232, I/O
	Modulation Frequency	Hz	1~20K
	Duty Cycle	%	5-95
	Modulation Rise/Fall Time (Min. Value)	μs	≤20
Aiming beam	Output Power	mW	≥2
	Center Wavelength	nm	635±10
Mechanical parameters	Dimensions (L×W×H)	mm	429*482*130
	Weight	kg	<15
Others	Cooling Method	-	Water cooling
	Cooling Capacity	W	≥500
	Cooling Water Temperature ⁽²⁾	°C	25±5
	Water Discharge	L/min	7
	Pipe Diameter (External)	mm	12
	Storage Temperature ⁽³⁾	°C	5~50
	Relative Humidity	%	5~80
	Safety Class	-	4 (EN 60825-01)

(1) Data measured under the operating condition with a power output of 300W at 25°C.

(2) Operating temperature defined by the package case. Acceptable operating range is 20°C~30°C, but performance may vary.


(3) A non-condensing environment is required for operation and storage.



Diode Laser System

DS3-41624-LD

Package Dimensions (mm)



OPERATING NOTES

- ◆ Avoid eye and skin exposure to direct radiation during operation.
- ◆ ESD precautions must be taken during storage, transportation and operation.
- ◆ Laser diode must work with good cooling.
- ◆ Operation temperature ranges from 20°C to 30°C .
- ◆ Storage temperature ranges from 5°C to 50°C.



Declaration: information and specifications contained herein are deemed to be reliable and accurate. BWT Beijing Ltd.reserves the right to change, alter or modify the design and specifications of these products at any time without notice.25-11